GOODWE

Maximising energy back-up for high-power PV rooftops

Optimised energy autonomy ____ Smart and efficient operations

Modern and compact design 😽 Highest safety standards

The trend of increasing PV module yield is influencing overall PV system requirements. At the forefront of development, GoodWe's ET inverters efficiently meet the needs of powerful solar rooftops to facilitate energy back-up, peak shaving and load management for optimised autonomy and reduced energy cost. The ET series can be combined with a range of battery capacities and brands, including the GoodWe Lynx Home F.

Peak shaving

UPS level switching <10ms



Powerful back-up overload



GOODWE

Technical Data	GW15K-ET	GW20K-ET	GW25K-ET	GW29.9K-ET
Battery Input Data				
Battery Type		Li-I	on	
Nominal Battery Voltage (V)	500			
Battery voltage range (V)	200 ~ 800			
Max. Continuous Charging Current (A)	50	50	50 × 2	50 × 2
Max. Continuous Discharging Current (A)	50	50	50 × 2	50 × 2
Max. Charging Power (W)	15000	20000	12500 × 2	15000 × 2
Max. Discharging Power (W)	15000	20000	12500 × 2	15000 × 2
PV String Input Data				
Max. Input Power (W)*1	22500	30000	37500	45000
Max. Input Voltage (V) ^{*2}		10		
MPPT Operating Voltage Range (V)	200 ~ 850			
Start-up Voltage (V)	200			
Nominal Input Voltage (V)	620			
Max. Input Current per MPPT (A)	30			
Max. Short Circuit Current per MPPT (A)		3		
Number of MPP Trackers	2	2	3	3
Number of Strings per MPPT	2/2	2/2	2/2/2	2/2/2
AC Output Data (On-grid)				
Nominal Apparent Power Output to Utility Grid (VA)	15000	20000	25000	29900
Max. Apparent Power Output to Utility Grid (VA)	16500	22000	27500	29900
Max. Apparent Power from Utility Grid (VA)	22500	30000	33000	33000
Nominal Output Voltage (V)	380 / 400, 3L / N / PE			
Nominal AC Grid Frequency (Hz)		50 /		
Max. AC Current Output to Utility Grid (A)*5	25.0	33.3	41.7	49.8
Max. AC Current From Utility Grid (A)	34.0	45.0	50.0	50.0
Power Factor Max. Total Harmonic Distortion		~1 (Adjustable from 0.8		
	<3%			
AC Output Data (Back-up)				
Back-up Nominal Apparent Power (VA)	15000	20000	25000	29900
Max. Output Apparent Power (VA)*3		20000 (24000@60s, 32000@3s)	25000 (30000@60s)	30000 (36000@60
Max. Output Current (A)	22.7 (27.3@60s, 36.4@3s)) 30.3 (36.4@60s, 48.5@3s)	37.9 (45.5@60s)	45.5 (54.5@60s)
Nominal Output Voltage (V)	380 / 400			
Nominal Output Freqency (Hz)	50 / 60 <3%			
Output THDv (@Linear Load)		<3	%	
Efficiency				
Max. Efficiency	98.0%			
European Efficiency	97.5%			
Max. Battery to AC Efficiency	97.5%			
MPPT Efficiency		99.	9%	-
Protection				
PV String Current Monitoring		Integ	rated	
PV Insulation Resistance Detection	Integrated			
Residual Current Monitoring	Integrated			
PV Reverse Polarity Protection	Integrated			
Battery Reverse Polarity Protection	Integrated Integrated			
Anti-islanding Protection AC Overcurrent Protection	Integrated			
AC Short Circuit Protection	Integrated			
AC Overvoltage Protection	Integrated			
DC Switch	Integrated			
DC Surge Protection	Type II			
AC Surge Protection	Type III Optional			
AFCI Remote Shutdown		Opti		
		integ		
General Data				
Operating Temperature Range (°C)		-35 ~		
Relative Humidity		0~9		
Max. Operating Altitude (m)		40 Smort Ear		
Cooling Method User Interface		Smart Far LED. WLA		
		LED, WLF RS485		
			185	
Communication with BMS		B 3/		
Communication with BMS Communication with Meter		WiFi	/ 4G	
Communication with BMS	48		/ 4G 54	54
Communication with BMS Communication with Meter Communication with Portal Weight (kg)	48	WiFi	54	54
Communication with BMS Communication with Meter Communication with Portal Weight (kg) Dimension (W × H × D mm) Noise Emission (dB)	48 <45	WiFi 48 520 × 66 <45	54 60 × 220 <45	54 <60
Communication with BMS Communication with Meter Communication with Portal Weight (kg) Dimension (W × H × D mm) Noise Emission (dB) Topology		WiFi 48 520 × 66 <45 Non-is	54 50 × 220 <45 olated	
Communication with BMS Communication with Meter Communication with Portal Weight (kg) Dimension (W × H × D mm) Noise Emission (dB) Topology Self-consumption at Night (W) ^{*4}		WiFi 48 520 × 66 <45 Non-is <	54 60 × 220 <45 olated 5	
Communication with BMS Communication with Meter Communication with Portal Weight (kg) Dimension (W × H × D mm) Noise Emission (dB) Topology		WiFi 48 520 × 66 <45 Non-is	54 50 × 220 <45 olated 5 56	

*5: For 400V grid, the Max. AC Current Output to Utility Grid is 23.9A for GW15K-ET, 31.9A for GW20K-ET, 39.9A for GW25K-ET, 43.3A for GW29.9K-ET. *: Please visit GoodWe website for the latest certificates.